

## New Jersey Department of Health and Senior Services

# HAZARDOUS SUBSTANCE FACT SHEET

Common Name: CHLOROPLATINIC ACID

CAS Number: 16941-12-1 DOT Number: UN 2507

\_\_\_\_\_

#### HAZARD SUMMARY

- \* Chloroplatinic Acid can affect you when breathed in.
- \* Contact can irritate the skin and eyes.
- \* Breathing Chloroplatinic Acid can irritate the nose and throat.
- \* Chloroplatinic Acid may cause a skin allergy. If allergy develops, very low future exposures can cause itching and a skin rash.
- \* Chloroplatinic Acid may cause an asthma-like allergy. Future exposures can cause asthma attacks with shortness of breath, wheezing, cough, and/or chest tightness.
- \* Repeated exposure can lead to permanent lung damage.
- \* Chloroplatinic Acid is a (HIGHLY) CORROSIVE CHEMICAL.

## **IDENTIFICATION**

**Chloroplatinic Acid** is a red-brown crystalline solid. It is used in electroplating, etching *zinc* for printing, making catalysts, and microscopy.

## **REASON FOR CITATION**

- \* Chloroplatinic Acid is on the Hazardous Substance List because it is regulated by OSHA and cited by ACGIH, NIOSH and DOT.
- \* This chemical is on the Special Health Hazard Substance List because it is **CORROSIVE**.
- \* Definitions are provided on page 5.

## HOW TO DETERMINE IF YOU ARE BEING EXPOSED

The New Jersey Right to Know Act requires most employers to label chemicals in the workplace and requires public employers to provide their employees with information and training concerning chemical hazards and controls. The federal OSHA Hazard Communication Standard, 1910.1200, requires private employers to provide similar training and information to their employees.

RTK Substance number: 0406

Date: September 1987 Revision: April 1998

-----

\* Exposure to hazardous substances should be routinely evaluated. This may include collecting personal and area air samples. You can obtain copies of sampling results from your employer. You have a legal right to this information under OSHA 1910.20.

\* If you think you are experiencing any work-related health problems, see a doctor trained to recognize occupational diseases. Take this Fact Sheet with you.

## WORKPLACE EXPOSURE LIMITS

\* The following exposure limits are for *Platinum*, *soluble salts*. (*measured as Platinum*):

OSHA: The legal airborne permissible exposure limit

(PEL) is  $0.002 \text{ mg/m}^3$  averaged over an 8-hour

workshift.

NIOSH: The recommended airborne exposure limit is

**0.002 mg/m<sup>3</sup>** averaged over a 10-hour workshift.

ACGIH: The recommended airborne exposure limit is

0.002 mg/m<sup>3</sup> which should not be exceeded at

any time.

## WAYS OF REDUCING EXPOSURE

- \* Where possible, enclose operations and use local exhaust ventilation at the site of chemical release. If local exhaust ventilation or enclosure is not used, respirators should be worn.
- \* Wear protective work clothing.
- \* Wash thoroughly <u>immediately</u> after exposure to **Chloroplatinic Acid** and at the end of the workshift.
- \* Post hazard and warning information in the work area. In addition, as part of an ongoing education and training effort, communicate all information on the health and safety hazards of **Chloroplatinic Acid** to potentially exposed workers.

This Fact Sheet is a summary source of information of <u>all potential</u> and most severe health hazards that may result from exposure. Duration of exposure, concentration of the substance and other factors will affect your susceptibility to any of the potential effects described below.

-----

#### **HEALTH HAZARD INFORMATION**

#### **Acute Health Effects**

The following acute (short-term) health effects may occur immediately or shortly after exposure to **Chloroplatinic Acid**:

- \* Contact can irritate the skin and eyes.
- \* Breathing **Chloroplatinic Acid** can irritate the nose and throat causing cough, sneezing and runny nose, and ulcers may develop in the inner nose.

#### **Chronic Health Effects**

The following chronic (long-term) health effects can occur at some time after exposure to **Chloroplatinic Acid** and can last for months or years:

#### **Cancer Hazard**

\* According to the information presently available to the New Jersey Department of Health and Senior Services, Chloroplatinic Acid has not been tested for its ability to cause cancer in animals.

#### **Reproductive Hazard**

\* According to the information presently available to the New Jersey Department of Health and Senior Services, Chloroplatinic Acid has not been tested for its ability to affect reproduction.

## **Other Long-Term Effects**

- \* Chloroplatinic Acid may cause a skin allergy. If allergy develops, very low future exposures can cause itching and a skin rash.
- \* Chloroplatinic Acid may cause an asthma-like allergy. Future exposures can cause asthma attacks with shortness of breath, wheezing, cough, and/or chest tightness.
- \* Repeated exposure can lead to permanent lung damage (pulmonary fibrosis).

#### **MEDICAL**

## **Medical Testing**

Before beginning employment and at regular times after that, the following are recommended:

\* Lung function tests. These may be normal if the person is not having an attack at the time of the test.

If symptoms develop or overexposure is suspected, the following may be useful:

\* Evaluation by a qualified allergist, including careful exposure history and special testing, may help diagnose skin allergy.

Any evaluation should include a careful history of past and present symptoms with an exam. Medical tests that look for damage already done are <u>not</u> a substitute for controlling exposure.

Request copies of your medical testing. You have a legal right to this information under OSHA 1910.20.

#### Mixed Exposures

\* Because smoking can cause heart disease, as well as lung cancer, emphysema, and other respiratory problems, it may worsen respiratory conditions caused by chemical exposure. Even if you have smoked for a long time, stopping now will reduce your risk of developing health problems.

#### WORKPLACE CONTROLS AND PRACTICES

Unless a less toxic chemical can be substituted for a hazardous substance, **ENGINEERING CONTROLS** are the most effective way of reducing exposure. The best protection is to enclose operations and/or provide local exhaust ventilation at the site of chemical release. Isolating operations can also reduce exposure. Using respirators or protective equipment is less effective than the controls mentioned above, but is sometimes necessary.

In evaluating the controls present in your workplace, consider: (1) how hazardous the substance is, (2) how much of the substance is released into the workplace and (3) whether harmful skin or eye contact could occur. Special controls should be in place for highly toxic chemicals or when significant skin, eye, or breathing exposures are possible.

In addition, the following control is recommended:

\* Where possible, automatically transfer **Chloroplatinic Acid** from drums or other storage containers to process containers.

Good **WORK PRACTICES** can help to reduce hazardous exposures. The following work practices are recommended:

\* Workers whose clothing has been contaminated by Chloroplatinic Acid should change into clean clothing promptly.

- \* Contaminated work clothes should be laundered by individuals who have been informed of the hazards of exposure to **Chloroplatinic Acid**.
- \* Eye wash fountains should be provided in the immediate work area for emergency use.
- \* If there is the possibility of skin exposure, emergency shower facilities should be provided.
- \* On skin contact with **Chloroplatinic Acid**, immediately wash or shower to remove the chemical. At the end of the workshift, wash any areas of the body that may have contacted **Chloroplatinic Acid**, whether or not known skin contact has occurred.
- \* Do not eat, smoke, or drink where Chloroplatinic Acid is handled, processed, or stored, since the chemical can be swallowed. Wash hands carefully before eating or smoking.
- \* Use a vacuum or a wet method to reduce dust during clean-up. DO NOT DRY SWEEP.
- \* When vacuuming, a high efficiency particulate absolute (HEPA) filter should be used, <u>not</u> a standard shop vacuum.

## PERSONAL PROTECTIVE EQUIPMENT

WORKPLACE CONTROLS ARE BETTER THAN PERSONAL PROTECTIVE EQUIPMENT. However, for some jobs (such as outside work, confined space entry, jobs done only once in a while, or jobs done while workplace controls are being installed), personal protective equipment may be appropriate.

OSHA 1910.132 requires employers to determine the appropriate personal protective equipment for each hazard and to train employees on how and when to use protective equipment.

The following recommendations are only guidelines and may not apply to every situation.

## Clothing

- \* Avoid skin contact with **Chloroplatinic Acid**. Wear protective gloves and clothing. Safety equipment suppliers/manufacturers can provide recommendations on the most protective glove/clothing material for your operation.
- \* All protective clothing (suits, gloves, footwear, headgear) should be clean, available each day, and put on before work.

## **Eye Protection**

\* Wear dust-proof goggles and face shield when working with powders or dust, unless full facepiece respiratory protection is worn.

## **Respiratory Protection IMPROPER USE OF RESPIRATORS IS DANGEROUS.**

Such equipment should only be used if the employer has a written program that takes into account workplace conditions, requirements for worker training, respirator fit testing and medical exams, as described in OSHA 1910.134.

- \* NIOSH has established new testing and certification requirements for negative pressure, air purifying, particulate filters and filtering facepiece respirators. The filter classifications of dust/mist/fume, paint spray or pesticide prefilters, and filters for radon daughters have been replaced with the N, R, and P series. Each series has three levels of filtering efficiency, 95%, 99%, and 99.9%. Check with your safety equipment supplier or your respirator manufacturer to determine which respirator is appropriate for your facility.
- \* If while wearing a filter, cartridge or canister respirator, you can smell, taste, or otherwise detect **Chloroplatinic Acid**, or in the case of a full facepiece respirator you experience eye irritation, leave the area immediately. Check to make sure the respirator-to-face seal is still good. If it is, replace the filter, cartridge, or canister. If the seal is no longer good, you may need a new respirator.
- \* Be sure to consider all potential exposures in your workplace. You may need a combination of filters, prefilters, cartridges, or canisters to protect against different forms of a chemical (such as vapor and mist) or against a mixture of chemicals.
- \* Where the potential exists for exposure over **0.002 mg/m³**, of *Platinum* or if the potential exists for overexposure to **Chloroplatinic Acid**, use a MSHA/NIOSH approved supplied-air respirator with a full facepiece operated in a pressure-demand or other positive-pressure mode. For increased protection use in combination with an auxiliary self-contained breathing apparatus operated in a pressure-demand or other positive-pressure mode.

  \* Exposure to **4 mg/m³** of *Platinum* is immediately
- \* Exposure to **4 mg/m³** of *Platinum* is immediately dangerous to life and health. If the possibility of exposure to *Platinum* above **4 mg/m³** exists, use a MSHA/NIOSH approved self-contained breathing apparatus with a full facepiece operated in a pressure-demand or other positive-pressure mode.

## **QUESTIONS AND ANSWERS**

- Q: If I have acute health effects, will I later get chronic health effects?
- A: Not always. Most chronic (long-term) effects result from repeated exposures to a chemical.
- Q: Can I get long-term effects without ever having short-term effects?
- A: Yes, because long-term effects can occur from repeated exposures to a chemical at levels not high enough to make you immediately sick.

- Q: What are my chances of getting sick when I have been exposed to chemicals?
- A: The likelihood of becoming sick from chemicals is increased as the amount of exposure increases. This is determined by the length of time and the amount of material to which someone is exposed.
- Q: When are higher exposures more likely?
- A: Conditions which increase risk of exposure include <u>dust</u> releasing operations (grinding, mixing, blasting, dumping, etc.), other physical and mechanical processes (heating, pouring, spraying, spills and evaporation from large surface areas such as open containers), and "confined space" exposures (working inside vats, reactors, boilers, small rooms, etc.).
- Q: Is the risk of getting sick higher for workers than for community residents?
- A: Yes. Exposures in the community, except possibly in cases of fires or spills, are usually much lower than those found in the workplace. However, people in the community may be exposed to contaminated water as well as to chemicals in the air over long periods. Because of this, and because of exposure of children or people who are already ill, community exposures may cause health problems.

\_\_\_\_\_

The following information is available from:

New Jersey Department of Health and Senior Services Occupational Disease and Injury Services Trenton, NJ 08625-0360 (609) 984-1863

#### **Industrial Hygiene Information**

Industrial hygienists are available to answer your questions regarding the control of chemical exposures using exhaust ventilation, special work practices, good housekeeping, good hygiene practices, and personal protective equipment including respirators. In addition, they can help to interpret the results of industrial hygiene survey data.

## Medical Evaluation

If you think you are becoming sick because of exposure to chemicals at your workplace, you may call a Department of Health and Senior Services physician who can help you find the services you need.

#### **Public Presentations**

Presentations and educational programs on occupational health or the Right to Know Act can be organized for labor unions, trade associations and other groups.

## **Right to Know Information Resources**

The Right to Know Infoline (609) 984-2202 can answer questions about the identity and potential health effects of chemicals, list of educational materials in occupational health, references used to prepare the Fact Sheets, preparation of the Right to Know survey, education and training programs, labeling requirements, and general information regarding the Right to Know Act. Violations of the law should be reported to (609) 984-2202.

\_\_\_\_\_

#### **DEFINITIONS**

**ACGIH** is the American Conference of Governmental Industrial Hygienists. It recommends upper limits (called TLVs) for exposure to workplace chemicals.

A carcinogen is a substance that causes cancer.

The **CAS number** is assigned by the Chemical Abstracts Service to identify a specific chemical.

A **combustible** substance is a solid, liquid or gas that will burn.

A **corrosive** substance is a gas, liquid or solid that causes irreversible damage to human tissue or containers.

**DEP** is the New Jersey Department of Environmental Protection.

**DOT** is the Department of Transportation, the federal agency that regulates the transportation of chemicals.

**EPA** is the Environmental Protection Agency, the federal agency responsible for regulating environmental hazards.

A fetus is an unborn human or animal.

A **flammable** substance is a solid, liquid, vapor or gas that will ignite easily and burn rapidly.

The **flash point** is the temperature at which a liquid or solid gives off vapor that can form a flammable mixture with air.

**HHAG** is the Human Health Assessment Group of the federal EPA.

**IARC** is the International Agency for Research on Cancer, a scientific group that classifies chemicals according to their cancer-causing potential.

A **miscible** substance is a liquid or gas that will evenly dissolve in another.

mg/m<sup>3</sup> means milligrams of a chemical in a cubic meter of air. It is a measure of concentration (weight/volume).

**MSHA** is the Mine Safety and Health Administration, the federal agency that regulates mining. It also evaluates and approves respirators.

A **mutagen** is a substance that causes mutations. A **mutation** is a change in the genetic material in a body cell. Mutations can lead to birth defects, miscarriages, or cancer.

**NAERG** is the North American Emergency Response Guidebook. It was jointly developed by Transport Canada, the United States Department of Transportation and the Secretariat of Communications and Transportation of Mexico. It is a guide for first responders to quickly identify the specific or generic hazards of material involved in a transportation incident, and to protect themselves and the general public during the initial response phase of the incident.

**NCI** is the National Cancer Institute, a federal agency that determines the cancer-causing potential of chemicals.

**NFPA** is the National Fire Protection Association. It classifies substances according to their fire and explosion hazard.

**NIOSH** is the National Institute for Occupational Safety and Health. It tests equipment, evaluates and approves respirators, conducts studies of workplace hazards, and proposes standards to OSHA.

**NTP** is the National Toxicology Program which tests chemicals and reviews evidence for cancer.

**OSHA** is the Occupational Safety and Health Administration, which adopts and enforces health and safety standards.

**PEOSHA** is the Public Employees Occupational Safety and Health Act, a state law which sets PELs for New Jersey public employees.

**ppm** means parts of a substance per million parts of air. It is a measure of concentration by volume in air.

A **reactive** substance is a solid, liquid or gas that releases energy under certain conditions.

A **teratogen** is a substance that causes birth defects by damaging the fetus.

**TLV** is the Threshold Limit Value, the workplace exposure limit recommended by ACGIH.

The **vapor pressure** is a measure of how readily a liquid or a solid mixes with air at its surface. A higher vapor pressure indicates a higher concentration of the substance in air and therefore increases the likelihood of breathing it in.

### >>>>>> E M E R G E N C Y I N F O R M A T I O N <<<<<<<<

Common Name: CHLOROPLATINIC ACID

DOT Number: UN 2507 NAERG Code: 154 CAS Number: 16941-12-1

| Hazard rating | NJDHSS | NFPA |
|---------------|--------|------|
| FLAMMABILITY  | 0      | -    |
| REACTIVITY    | 1      | -    |

**CORROSIVE** 

POISONOUS GASES ARE PRODUCED IN FIRE

Hazard Rating Key: 0=minimal; 1=slight; 2=moderate; *3=serious; 4=severe* 

## FIRE HAZARDS

- Use dry chemical, CO<sub>2</sub>, water spray, or foam extinguishers.
- Chloroplatinic Acid may burn, but does not readily ignite.
- POISONOUS GASES ARE PRODUCED IN FIRE
- If employees are expected to fight fires, they must be trained and equipped as stated in OSHA 1910.156.

#### SPILLS AND EMERGENCIES

If **Chloroplatinic Acid** is spilled, take the following steps:

- Evacuate persons not wearing protective equipment from area of spill until clean-up is complete.
- Collect powdered material in the most convenient and safe manner and deposit in sealed containers.
- Ventilate the area of spill or leak after clean-up is complete.
- It may be necessary to contain and dispose of Chloroplatinic Acid as a HAZARDOUS WASTE. Contact your Department of Environmental Protection (DEP) or your regional office of the federal Environmental Protection Agency (EPA) for specific recommendations.
- If employees are required to clean-up spills, they must be properly trained and equipped. OSHA 1910.120(q) may be applicable.

FOR LARGE SPILLS AND FIRES immediately call your fire department. You can request emergency information from the following:

CHEMTREC: (800) 424-9300 NJDEP HOTLINE: (609) 292-7172

## HANDLING AND STORAGE

- Prior to working with Chloroplatinic Acid you should be trained on its proper handling and storage.
- Store in tightly closed containers in a cool, well-ventilated area.

## FIRST AID

#### In NJ, POISON INFORMATION 1-800-764-7661

#### **Eve Contact**

\* Immediately flush with large amounts of water for at least 15 minutes, occasionally lifting upper and lower lids.

## **Skin Contact**

Quickly remove contaminated clothing. Immediately wash contaminated skin with large amounts of water.

## **Breathing**

- Remove the person from exposure.
- Begin rescue breathing if breathing has stopped and CPR if heart action has stopped.
- Transfer promptly to a medical facility.

## PHYSICAL DATA

**Vapor Pressure:** Essentially zero at 68°F (20°C)

Water Solubility: Soluble

#### OTHER COMMONLY USED NAMES

#### Chemical Name:

Platinate, Hexachloro-, Dihydrogen-

#### Other Names:

Hexachloroplatinic Acid; Platinic Chloride

Not intended to be copied and sold for commercial purposes.

NEW JERSEY DEPARTMENT OF HEALTH AND SENIOR SERVICES

## Right to Know Program

PO Box 368, Trenton, NJ 08625-0368

(609) 984-2202